

Declaration of Performance - No: 232-2021-117

according to Annex III Construction Products Regulation (305/2011/EU)
and Regulation (EU) No 574/2014

for the construction product	<i>Rolled plates</i>
1. Unique identification code of the product type:	<i>S460M+Z35 - EN 10025- 4:2019</i>
2. Intended use:	<i>Rolled plates for use in the construction products</i>
3. Manufacturer:	<i>PRIVATE JOINT STOCK COMPANY «AZOVSTAL IRON & STEEL WORKS» 1, Leporskogo Str., Mariupol, Donetsk region, Ukraine, 87505 Fax: +38 (0629) 52-70-00, E-mail: azovstal@metinvestholding.com, http://azovstal.metinvestholding.com</i>
4. Authorised representative:	<i>No</i>
5. System of AVCP:	<i>System 2+</i>
6. Harmonised standard: Notified body:	<i>EN 10025- 1:2004 TÜV NORD Systems GmbH & Co. KG Germany-22525 Hamburg , Kenn.Nr. 0045</i>

7. Declared performance:


Essential characteristics	Performance										Harmonized technical specification	
	Dimensions and shape	Chemical composition	Carbon equivalent, %	Thickness, mm	Minimum yield strength, Mpa	Tensile strength, Mpa	Minimum elongation, % (Lo=5.65√So)	Through-thickness reduction of area (Z), min, %	Impact energy (KV) on longitudinal specimens, at temperature			
									T, °C	KV, J, min		
Maximum deviations on dimensions and shape Yield strength Tensile strength Elongation Impact energy Weldability Durability	EN 10029:2011-02 Tables 1, 2, 3, 4	EN 10025-4:2019 Table 1&2	≤0,46	>16≤40	440	540-720	17	25	-20	40	EN 10025-1:2004	
			≤0,47	>40≤52	430	530-710	17	25	-20	40		

The performance of the product identified above is in conformity with the set of declared performance.

This Declaration of Performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:
Dmytro S. Zolov, Director for Technology and Quality

Mariupol, 14.12.2021



To review the Declaration of Performance please refer to:
<https://azovstal.metinvestholding.com/en/activity/quality/declarations-of-performance>